

## Product sheet

## MCCB 2P 10A C Curve 2 Modules 230V

Brand: LEGRAND

Reference: LEGRAND 449934



2-pole miniature circuit breaker with a rated current of 10 A and C tripping curve. Protects installations against overloads and short circuits, with a breaking capacity of 10 kA at 230 V. Occupies 2 modules and accepts cables from 1.5 to 35 mm<sup>2</sup>.

[View product online](#)

### Description

2-pole miniature circuit breaker designed to protect electrical installations against overloads and short circuits. It also allows for the control and isolation of the installation when necessary. Its compact 2-module design facilitates integration into standard electrical panels.

#### Technical features

- Rated current: 10 A
- Tripping curve: C
- Rated voltage: 230 V AC
- Breaking capacity: 10 kA at 230 V and 6 kA at 400 V
- Rated insulation voltage (Ui): 500 V
- Rated impulse voltage (Uimp): 4 kV
- Frequency: 50...60 Hz
- Protection rating: IP20
- Operating temperature: -25...70 °C
- Cable cross-section: 1.5...35 mm<sup>2</sup> (rigid)
- Depth: 44 mm

This device provides a reliable response to electrical faults, ensuring the safety of connected circuits. The C curve offers an appropriate balance between tolerance to starting peaks and rapid protection against short circuits. Its flush installation optimizes the available space in the panel.

Specifications

|                     |               |
|---------------------|---------------|
| Rated current (A)   | 10            |
| Curve               | C             |
| EAN                 | 3414972963596 |
| Manufacturer        | LEGRAND       |
| No. of poles        | 2P            |
| Depth               | 44 mm         |
| Protection          | IP20          |
| Rated voltage       | 230           |
| Nominal voltage (V) | 230 V         |

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 26 October 2026