

Product sheet

Circuit Breaker 2P 32A C Curve 230V 2 Modules

Brand: LEGRAND

Reference: LEGRAND 449938



2-pole miniature circuit breaker with a rated current of 32 A and C tripping curve. Protects installations against overloads and short circuits, with a breaking capacity of 10 kA at 230 V. Occupies 2 modules, has a depth of 44 mm and IP20 protection rating. Compatible with cables from 1.5 to 35 mm².

[View product online](#)

Description

2-pole miniature circuit breaker designed to protect electrical installations against overloads and short circuits. It also allows for the control and isolation of the installation. Its compact design occupies 2 modules and is intended for flush mounting.

Technical features

- Rated current: 32 A
- Tripping curve: C
- Nominal voltage: 230V~ / 400V
- Breaking capacity: 10 kA at 230V and 6 kA at 400V (EN 60898)
- Frequency: 50...60 Hz
- Construction depth: 44 mm
- Protection rating: IP20
- Operating temperature: -25...70 °C
- Cable cross-section: 1.5...35 mm² (rigid)
- Current limiting class: 3

This device offers a reliable response to electrical faults, ensuring the safety of the network. Its high breaking capacity and C curve make it suitable for loads with moderate starting peaks.

Specifications

Rated current (A)	32
Curve	C
EAN	3414972963718
Manufacturer	LEGRAND
No. of poles	2P
Protection	IP20

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 27 October 2026