

Product sheet

Reducing ball valve 1/2" hexagonal PN-16

Brand: GENE BRE

Reference: GEN 3096 04



Mini dial valve with reduced 1/2" step and maximum 16 bar pressure. Brass body chromed according to UNE-EN 12165 and threaded connections female gas ISO 228/1. Operating range from -20oC to 140oC, PTFE seats and aluminium handle for precise flow control.

[View product online](#)

Description

Mini sphere valve with reduced 1/2" step, designed for flow control in pipe systems. Its chromed brass construction guarantees an aesthetic appearance and a solid base for industrial or domestic applications where precision in cutting is required.

Technical characteristics

- Nominal diameter: 1/2".
- Maximum working pressure: 16 bar (PN-16).
- Body material: Brass according to UNE-EN 12165 standard, chrome finish.
- Connections: Female gas threaded extremities (BSP) according to ISO 228/1.
- Working temperature range: from -20oC to 140oC.
- Action: Aluminium handle.
- Seat material: PTFE.

The combination of PTFE seats and brass body allows smooth operation and reliable watertightness within the specified temperature range. The compact mini design facilitates installation in reduced spaces, while the aluminium handle offers ergonomic and lightweight handling for opening and closing the passage.

Specifications

EAN	8428381007807
Manufacturer	Genebre

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 29 October 2026