

Product sheet

Polypropylene stop sleeve diameter 75 mm

Brand: Italsan

Reference: ITAL VS0650857



Polypropylene stopper sleeve, triple layer, with intermediate mineral reinforcement. Nominal diameter of 75 mm for waste drainage at low and high temperatures, ventilation and evacuation of rainwater by gravity in plumbing systems.

[View product online](#)

Description

Copolymer polypropylene stopper sleeve designed for connection of drainage tubes. Its triple layer structure includes an intermediate layer of PE reinforced with mineral load, optimized for fluid handling in gravity evacuation systems.

Technical characteristics

- Material: Polypropylene triple layer copolymer.
- Intermediate layer: PP reinforced with mineral load.
- Nominal diameter: 75 mm
- Implementation: Waste water drain at low and high temperatures.
- Additional use: Ventilation and evacuation of rainwater by gravity.

This component allows to manage waste water with temperature variations and to evacuate rainwater by gravity. The composition of the material meets the requirements of these specific flows, ensuring the functionality required in the installation.

Specifications

EAN	8023857224896
Manufacturer	Italsan
Material	Polypropylene
Measures	75 mm

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 27 October 2026