

Product sheet

Trielle LED Panel 60x60 cm 42 W Flicker Free

Brand: LEDME

Reference: LEDME LM5388



60x60 cm led panel with 42 W power, Epistar light source and 100 lm/W efficiency. It has 3CCT colour temperature, 120° beam angle, 0.95 power factor and IP40 protection. Compatible with power supply 170-265 V AC, operating between -20°C and +45°C.

[View product online](#)**Description**

60x60 cm led panel with 42 W power, designed for general lighting in interior spaces. Ideal for office facilities, corridors or shopping areas, it offers a uniform light without blinking thanks to Flicker Free technology. Compatible with 170-265 V AC voltages and 50/60 Hz frequencies, ensuring stability in different electrical conditions.

Technical characteristics

- Mark: M LEDME
- Watts: 42 W
- Light Source: Epistar
- Luminosity: 4200 lm
- Efficiency: 100 lm/W
- Working temperature: -20°C ~ +45°C
- View angle: 120°
- Lifetime: 30,000 hours
- Protection: IP40
- Impact index: IK5
- Electrical insulation class: II
- Overvoltage protection: 4 kV
- Overload protection: Yes
- Short circuit protection: Yes
- Power supply: 170-265 V AC

- Frequency: 50/60 Hz
- Dimensions: 595 x 595 x 35 mm
- Material: Aluminium
- Driver: Philips
- chromatic reproduction index (CRI): 80
- UGR: <19
- Power factor: 0.95
- Flicker Free: Yes
- Regulatory: Optional
- Guarantee: 5 years
- Color temperature: 3CCT

Specifications

Frequency	50/60 Hz
Insulation voltage	Clase II
Cri (Ra)	80
Driver included	Yes
EAN	8435579753880
Manufacturer	Ledme
Lumens (lm)	4200 lm
Material	Aluminio
Nominal voltage (V)	170-265 V ac
Current type	AC
Type of lamp	LED
Usage	Indoor

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 12 October 2026