Product sheet

# Kaedra Surface Distribution Box 8 Modules

Brand: SCHNEIDER

Reference: IMPO 13154M



Sealed Kaedra distribution box, surface mounting, with 4 openings and capacity for 8 modules of 18 mm. Designed for industrial environments, it offers double insulation (Class II), IP65 protection, and IK09 resistance. Includes a terminal block with 8 terminals, 4 power outlets of 65 x 85 mm, and cable management support.

View product online

## Description

Sealed cofret-type distribution box from the Kaedra range, designed for surface mounting with 4 openings and capacity for 8 modules of 18 mm in a single row. Ideal for electrical installations in industrial or outdoor environments requiring protection against dust and water.

Technical Features

- Number of 18 mm modules: 8
- Number of horizontal rows: 1
- Spacing of 9 mm: 16
- Number of openings in the interface: 4
- Rated current [In]: 63 A
- Electrical insulation class: Double insulation Class II
- Protection degree IP: IP65 according to IEC 60529
- Impact protection degree IK: IK09 according to IEC 62262
- Fire resistance: 750 °C according to IEC 60695-2-1
- Operating ambient temperature: -25…60 °C
- Overvoltage category: II
- Housing material: Self-extinguishing polymer
- Power dissipation: 15 W
- Rail type: DIN
- Number of PG ISO knockouts: 7

- Number of terminal blocks: 1 with clamping capacity: 8 terminals
- Distribution block outputs: 4 x 10 mm², 4 x 16 mm²
- Color: Transparent green door, light gray housing (RAL 7035)
- Environmental characteristics: UV resistance, class 3 according to ISO 4582:2010 and ISO 4892-2:2013
- Standards: IEC 60695, IEC 60439-3, EN 50262
- Unlocking: Optional lock

The product includes 1 pushbutton control plate, 4 power outlet plates of 65 x 85 mm, 1 terminal block with 8 terminals, 2 cable bars, 1 terminal block support, and 2 cable clamps. Mounting plate not included.

## Specifications

| | |
|---|---|
| Insulation voltage | Clase II |
| Rated current (A) | 63 |
| EAN | 3606486528846 |
| Manufacturer | SCHNEIDER |
| Range | Industrial |
| Long | 160 mm |
| Length | 1 |
| Material | Polímero |
| Measures | 160 x 85 mm |
| Weight (kg) | 2.5 kg |
| Power (W) | 15 W |
| Maximum power (W) | 15 W |
| Depth | 85 mm |
| Protection | IP65 |
| Cable cross-section (mm²) | 10 mm² |

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 25 November 2026