

Product sheet

Kaedra surface-mounted watertight box 1 row 4 modules IP65

Brand: SCHNEIDER

Reference: IMPO 13957M



Mini Kaedra is a surface watertight box with 4 18 mm modules in a single row, designed for facilities in residential environments and small shops. Made of self-extinguishing polymer, it offers IP65 protection and IK09 protection degree.

[View product online](#)

Description

Mini Kaedra is a mini-enveloping case for modular devices, designed for surface installation. Ideal for residential environments and small shops, it offers IP65 protection and IK09 resistance, ensuring durability in adverse conditions.

Technical characteristics

- Number of 18 mm modules per row: 4
- Total number of 18 mm modules: 4
- Number of horizontal rows: 1
- Steps of 9 mm: 8
- Cabinet mounting: Area
- Rail type: DIN
- Nominal current [In]: 63 A
- Power dissipation: 10 W
- Degree of IP protection: IP65 according to Enable / Deactivate Ig
- Level of protection IK: IK09 according to H
- Fire resistance: 750 °C according to IEC 60695-2-1
- UV resistance: State 1, Class 3 according to ISO 4582:2010
- Ultraviolet degradation test: according to ISO 4892-2:2013
- Overvoltage category: II
- Operating ambient temperature: -25...60 °C

- Electrical insulation class: Double isolation Class II
- Envelope material: Self-extinguishing polymer
- Colour: Clear green door, light grey envelope (RAL 7035)
- Number of dies PG ISO: 3
- Description of locking options: Optional lock
- Accessories included: 1 terminal block holder, 1 marking kit
- Mounting plate: With slots
- Height: 200 mm
- Width: 123 mm
- Depth: 112 mm
- Internal depth: 56 mm
- Standards: IEC 670 H, IEC 60439-3, EN 50262
- EU RoHS Directive: Proactive (out-of-scope) compliance
- RoHS China Regulations: Outside the scope
- REACH Regulation: No SVHC
- No mercury: Yes
- Information on RoHS exemptions: Yes

Specifications

High	200 mm
Rated current (A)	63
Width	123 mm
EAN	3606486529010
Manufacturer	SCHNEIDER
Intensity	10
Long	200 mm
Material	Polímero
Measures	200 mm x 123 mm x 112 mm
Weight (kg)	1.5 kg
Power (W)	10 W
Maximum power (W)	10 W
Depth	112 mm
Protection	IP65

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 11 October 2026