Product sheet

Kaedra Sealed Box 1 Row 12 Modules

Brand: SCHNEIDER

Reference: IMPO 13962M



Kaedra sealed box, surface mounting, 1 row with 12 modules of 18 mm, made of self-extinguishing polymer. Class II insulation, IP65 and IK09 protection. Supports nominal current of 63 A, operating temperature -25 to 60 °C.

View product online

Description

Kaedra surface-mounted sealed box with 1 row and 12 modules, designed for electrical installations in residential and small commercial environments. Its self-extinguishing polymer structure offers high mechanical strength and fire resistance up to 750 °C.

Technical Features

- Number of 18 mm modules per row: 12
- Total number of 18 mm modules: 12
- Number of horizontal rows: 1
- Spacing of 9 mm: 24
- Rated current [In]: 63 A
- Electrical insulation class: Class II (Double insulation)
- Protection degree IP: IP65 according to IEC 60529
- Protection degree IK: IK09 according to IEC 62262
- Fire resistance: 750 °C according to IEC 60695-2-1
- Housing material: Self-extinguishing polymer
- Operating ambient temperature: -25…60 °C
- Overvoltage category: II
- Power dissipation: 24 W
- Mounting type: Surface
- Rail type: DIN
- Number of PG ISO knockouts: 17

- Color: Transparent green door, light gray housing (RAL 7035)
- Environmental characteristics: UV resistance, class 3 according to ISO 4582:2010 and ISO 4892-2:2013
- Standards: EN 50262, IEC 60439-3, IEC 670
- Included accessories: 1 cable strip, 1 marking kit, 1 terminal block holder, 1 terminal block with 8 holes
- Distribution block outlets: 4 x 10 mm^2, 4 x 16 mm^2
- Mounting plate description: With slots
- Faceplate type: Reversible transparent
- Locking options: Optional lock
- EU RoHS Directive: Proactive compliance (out of scope)
- China RoHS Regulation: Outside scope
- REACH Regulation: No SVHC
- Mercury-free: Yes

Specifications

High	120 mm
Rated current (A)	63
Width	85 mm
Colour	Gris claro
EAN	3606486529058
Manufacturer	SCHNEIDER
Long	120 mm
Material	Polímero
Measures	120x85 mm
# Elements	12
Weight (kg)	2.4 kg
Power (W)	24 W
Depth	85 mm
Protection	IP65

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 25 November 2026