

Product sheet

Vigi Block 2P 63A 30mA NG125 type AC

Brand: SCHNEIDER

Reference: IMPO 19000



Vigi NG125 2P block with nominal current 63 A, earth leakage sensitivity 30 mA, type AC, instantaneous protection. Designed for installations in small businesses, compatible with 35 mm DIN rail mounting.

[View product online](#)

Description

Vigi NG125 2P block with nominal current of 63 A and earth leakage sensitivity of 30 mA, designed to protect circuits in electrical installations of small businesses. Its independent voltage trip technology allows instantaneous response to current leakage, ensuring safety in environments with AC 50/60 Hz supply and operating voltages between 230 and 415 V AC.

Technical features

- Number of poles: 2P
- Nominal current [In]: 63 A
- Network type: AC
- Earth leakage sensitivity: 30 mA
- Protection delay: Instantaneous
- Leakage protection class: Type AC
- System location: Output
- Network frequency: 50/60 Hz
- Nominal operating voltage [Ue]: 230...415 V AC 50/60 Hz
- Tripping technology: Voltage-independent
- Nominal insulation voltage [Ui]: 690 V AC 50/60 Hz according to En> 50 A
- Voltage impulse withstand [Uimp]: 8 kV according to En> 50 A
- Mounting support: Symmetrical 35 mm DIN rail
- Electrical connection to MCB: Via screws
- Spacing: 9 mm

- Height: 118 mm
- Width: 99 mm
- Depth: 81 mm
- Weight: 0.25 kg
- Electrical durability: 10000 cycles according to En> 50 A
- Connections - terminals: Tunnel type 1...35 mm² flexible, 1.5...50 mm² rigid
- Cable stripping length: 20 mm
- Tightening torque: 3.5 N·m
- Product compatibility: Terminal
- Compatibility code: VLS
- Standards: En> 50 A
- Protection degree IP: IP40 according to En> 50 A
- Contamination degree: 3 according to En> 50 A
- Electromagnetic compatibility: Impulse resistance 8/20 µs, 3000 A according to En> 50 A
- Tropicalization: 2 according to IEC 60068-1
- Relative humidity: 95 % at 55 °C
- Maximum operating altitude: 2000 m
- Sustainable offering status: Green Premium product
- REACH regulation: Does not contain SVHC
- EU RoHS directive: Compliant
- Mercury-free: Yes
- RoHS exemptions: Yes
- China RoHS regulation: Product outside the scope of China RoHS
- WEEE: Must be disposed of according to specific collection system in the EU

Specifications

Frequency	50/60 Hz
Rated current (A)	63
Width	9,9 cm
Class	AC
Sensitivity	30 mA
EAN	3303430190004
Manufacturer	SCHNEIDER
Long	11,8 cm
No. of poles	2P
Weight (kg)	0,25
Depth	8,1 cm
Protection	IP40
Rated voltage	230

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 14 October 2026