Product sheet

Interpact INS63 4P Isolating Switch

Brand: SCHNEIDER

Reference: IMPO 28903



Compact isolating switch Interpact INS63 4P, designed for industrial applications with a rated current of 63 A in AC-22A and DC-22A, rated operating voltage of 500 V AC and 250 V DC, short-circuit breaking capacity of 15 kA at 500 V AC, pollution degree 3, DIN rail mounting, with position indicator and rotary handle, compliant with RoHS and certified KEMA-KEUR.

View product online

Description

Compact isolating switch Interpact INS63 4P from the ComPact range, designed for safe disconnection of electrical circuits in industrial and commercial installations.

Specifications

Frequency	50/60 Hz
Rated current (A)	63
Width	90 mm
Colour	Black
EAN	3303430289036
Manufacturer	SCHNEIDER
Range	Industrial
Long	85 mm
Measures	85 mm x 90 mm x 62,5 mm
# Elements	4
No. of poles	4P
Depth	62,5 mm
Protection	IP40
Nominal voltage (V)	500 V
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 25 November 2026