

Product sheet

4P Isolating Switch ComPact Interpact INS160

Brand: SCHNEIDER

Reference: IMPO 28913



4P isolating switch ComPact Interpact INS160, designed for industrial applications with DIN rail mounting. Supports nominal current of 160 A in AC-22A and 100 A in AC-23A, nominal operating voltage up to 690 V AC and 250 V DC. Features rotary operation, contact position indicator, and protection rating IP40, IK07. Mechanical durability of 15,000 cycles and short-circuit capacity of 154 kA with upstream circuit breaker.

[View product online](#)

Description

4P isolating switch from the ComPact Interpact INS160 range, designed for control and isolation of electrical circuits in industrial installations. Its DIN rail mounting and fixed structure make it suitable for power distribution in electrical enclosures.

Specifications

Frequency	50/60 Hz
Rated current (A)	160
Width	135 mm
EAN	3303430289135
Manufacturer	SCHNEIDER
Range	Industrial
Long	100 mm
No. of poles	4P
Weight (kg)	0,9 kg
Depth	62,5 mm
Protection	IP40
Nominal voltage (V)	690
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 9 October 2026