

Product sheet

Recessed socket Pratika 2P+E 16 A grey

Brand: SCHNEIDER

Reference: IMPO 81141



Waterproof socket with flange from the PratiKa range, designed for surface panel installation, with 2P+E connection, 16 A (10 A) rated current, 250 V AC operating voltage, 50/60 Hz frequency, German household standard, self-extinguishing polymer housing, stainless steel contacts, IP65 and IK09 protection grade, 850 °C resistant.

[View product online](#)

Description

Embossable socket with flange from the PratiKa range, designed for surface panel installation. Compatible with German household standard, it offers a secure connection for electrical devices in residential or commercial environments. Its structure is built with self-extinguishing engineering polymer and stainless steel contacts to ensure durability and electrical safety.

Technical characteristics

- Number of poles: 2P+E
- Network type: AC
- Output standard: German Domestic
- Nominal current: 16 A / 10 A
- Network frequency: 50/60 Hz
- Nominal employment voltage: 250 V
- Housing material: Self-extinguishing engineering polymer
- Contact material: Pines and springs in stainless steel
- Degree of IP protection: IP65
- Level of protection IK: IK09
- Fire resistance: 850 °C
- Operating ambient temperature: -25...40 °C
- Relative humidity: 50 % at 40 °C, 70 % at 30 °C, 90 % at 20 °C

- Standards: IEC 60884
- Assembly: Surface / panel mounted
- Number of sockets: 1
- Connections: Screws, screws and screws
- Base size: 80 x 80 x 45 mm
- Height: 85 mm
- Width: 65 mm
- Depth: 45.2 mm
- Weight: 0.112 kg
- Colour: Grey (RAL 7035)
- Compatibility code: Take Pratika.

Robust design and resistant materials allow its use in demanding environments, ensuring a reliable and secure connection. Its construction in self-extinguishing polymer and fire resistance increase safety in case of overheating.

Specifications

Frequency	50/60 Hz
Rated current (A)	16
Width	65 mm
Colour	Grey
EAN	3303430811411
Manufacturer	SCHNEIDER
Material	Polímero
No. of poles	2P+E
Weight (kg)	0,112 kg
Depth	45,2 mm
Protection	IP65
Nominal voltage (V)	250 V
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 10 October 2026