

Product sheet

Acti9 iC60N 3P 20 A C Curve Magnetic Thermal Switch

Brand: SCHNEIDER

Reference: IMPO A9F77320



Three-phase magnetic thermal switch with a rated current of 20 A and C curve, breaking capacity Icn 6000 A at 400 V AC, compact design with a width of 54 mm, DIN rail mounting, thermal and magnetic protection according to IEC 60898-1 and EN 60898-1 standards, pollution degree 3, service category A, and 6 kV surge voltage resistance.

[View product online](#)

Description

Miniature three-phase magnetic thermal switch designed to protect electrical circuits in industrial and commercial installations. Provides thermal and magnetic protection through thermal-magnetic technology, with a rated current of 20 A and C curve, suitable for motor starting and inductive loads. Compatible with AC and DC networks, with a breaking capacity Icn of 6000 A at 400 V AC, compliant with IEC 60898-1 and EN 60898-1 standards.

Specifications

Frequency	50/60 Hz
Rated current (A)	20
Width	54 mm
Colour	White
Curve	C
EAN	3606480094231
Manufacturer	SCHNEIDER
Range	Industrial
Long	85 mm
Halogen-free	Yes
Measures	85 mm x 54 mm x 78,5 mm
No. of poles	3P
Weight (kg)	0,375 kg
Depth	78,5 mm

Protection	IP20
Cable cross-section (mm²)	16 mm²
Rated voltage	400
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 12 October 2026