

Product sheet

Acti9 iC60N 4P 25 A C Curve Magnetic Thermal Switch

Brand: SCHNEIDER

Reference: IMPO A9F77425



4P modular magnetic thermal switch with a rated current of 25 A, C curve, and breaking capacity I_{cn} of 6000 A at 400 V AC. Designed for overload and short-circuit protection in industrial and commercial installations. Complies with IEC 60898-1 and EN 60898-1 standards, with IP20 protection rating and category IV overvoltage classification.

[View product online](#)

Description

4P modular magnetic thermal switch with a rated current of 25 A and C curve, designed for overload and short-circuit protection in industrial and commercial electrical installations. Compatible with AC and DC networks, using thermal-magnetic tripping technology.

Specifications

Rated current (A)	25
Width	72 mm
Curve	C
EAN	3606480094330
Manufacturer	SCHNEIDER
Range	Industrial
Halogen-free	Yes
No. of poles	4P
Weight (kg)	0,5 kg
Depth	78,5 mm
Protection	IP20
Cable cross-section (mm ²)	16 mm ²
Rated voltage	400
Nominal voltage (V)	220...240 V AC 50/60 Hz, 400 V AC 50/60 Hz, 380...415 V AC 50/60 Hz, 440 V AC 50/60 Hz, 125...180 V corriente continua

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 10 October 2026