

## Product sheet

# Acti9 iC60H 4P 40 A C Curve Miniature Circuit Breaker

Brand: SCHNEIDER

Reference: IMPO A9F87440



Miniature circuit breaker 4P, 40 A, C curve, with breaking capacity of 15 kA at 380-415 V AC 50/60 Hz, compliant with IEC 60898-1 and IEC 60947-2. Offers thermal and magnetic protection via thermal-magnetic technology, DIN rail mounting, position and trip indicator, resistance to voltage surges of 6 kV, pollution degree 3, and overvoltage category IV.

[View product online](#)

## Description

Miniature 4P circuit breaker with thermal and magnetic protection, designed for electrical circuits in industrial and commercial installations. Offers breaking capacity of 15 kA at 380-415 V AC 50/60 Hz, compliant with IEC 60898-1 and IEC 60947-2.

## Specifications

|                     |                                                                                                                                       |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Frequency           | 50/60 Hz                                                                                                                              |
| Rated current (A)   | 40                                                                                                                                    |
| Width               | 72 mm                                                                                                                                 |
| Colour              | White                                                                                                                                 |
| Curve               | C                                                                                                                                     |
| EAN                 | 3606480096150                                                                                                                         |
| Manufacturer        | SCHNEIDER                                                                                                                             |
| Range               | Industrial                                                                                                                            |
| Halogen-free        | Yes                                                                                                                                   |
| Measures            | 85 mm x 72 mm x 78,5 mm                                                                                                               |
| No. of poles        | 4P                                                                                                                                    |
| Weight (kg)         | 0,5 kg                                                                                                                                |
| Depth               | 78,5 mm                                                                                                                               |
| Protection          | IP20                                                                                                                                  |
| Nominal voltage (V) | 220...240 V AC 50/60 Hz, 400 V AC 50/60 Hz, 380...415 V AC 50/60 Hz, 440 V AC 50/60 Hz, 12...133 V AC 50/60 Hz, 180...250 V corriente |

|              |          |
|--------------|----------|
|              | continua |
| Current type | AC       |

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 11 October 2026