

Product sheet

Acti9 iC40 3P+N 40A 300mA Vigi Module

Brand: SCHNEIDER

Reference: IMPO A9Y63740



Vigi module iC40 3PN 40A 300mA AC, with instantaneous earth leakage protection type AC, nominal operating voltage 400 V AC 50 Hz, rated current 40 A, terminal screw connection, DIN rail mounting, protection degree IP20, compatible with Acti9 iDT40 range, white design, resistant to voltage surges of 4 kV.

[View product online](#)

Description

Vigi module from the Acti9 range, designed for protection against current leakage in single-phase or three-phase electrical installations with neutral. Installed at the output of the system, it provides instantaneous protection against AC-type residual currents with a sensitivity of 300 mA.

Technical Features

- Number of poles: 3P + N
- Neutral position: Left
- Rated current [In]: 40 A
- Nominal operating voltage [Ue]: 400 V AC 50 Hz
- Nominal insulation voltage [Ui]: 440 V AC 50/60 Hz
- Surge voltage withstand [Uimp]: 4 kV
- Earth leakage sensitivity: 300 mA
- Protection delay: Instantaneous
- Protection class: Type AC
- Tripping technology: Voltage-independent
- Supply frequency: 50 Hz
- Protection degree IP: IP20
- Connections: Lower tunnel terminal (1...16 mm² rigid, 1...10 mm² flexible)
- Cable stripping length: 14 mm
- Tightening torque: 2 N·m

- Height: 99.5 mm
- Width: 93 mm
- Depth: 74 mm
- Color: White
- Mechanical durability: 20000 cycles
- Electrical durability: 10000 cycles
- Operating ambient temperature: -5...60 °C
- Storage ambient temperature: -40...85 °C
- Maximum operating altitude: 2000 m
- Contamination degree: 3
- Relative humidity: 95 % at 55 °C
- Standards: EN/IEC 61009-2-1
- On-site indicators: Error indication
- Mounting support: DIN rail
- Electrical connection to MCB: Screw terminals
- 9 mm steps: 4
- Certifications: CE, NF
- Sustainable offering status: Green Premium product
- EU RoHS Directive: Compliant
- REACH Regulation: No SVHC
- RoHS exemptions: Yes
- China RoHS regulation: Not applicable
- Waste electrical and electronic equipment (WEEE): Disposal according to specific system in EU
- Halogen presence: No halogens

Specifications

Frequency	50
High	99,5 mm
Rated current (A)	40
Width	93 mm
Class	AC
Colour	White
Sensitivity	300 mA
EAN	3606481383631
Manufacturer	SCHNEIDER
Halogen-free	Yes
No. of poles	3P+N
Depth	74 mm
Protection	IP20
Rated voltage	400

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 11 October 2026