

Product sheet

Kaedra Sealed Enclosure 1x4 Module 63 A Transparent

Brand: SCHNEIDER

Reference: IMPO 13151M



Mini sealed enclosure of Mureva type, surface-mounted design, with 1 row of 4 modules of 18 mm, 2 openings of 65x85 mm, IP65 and IK09 protection, Class II electrical insulation, nominal current capacity 63 A, made of self-extinguishing polymer, compliant with IEC 60439-3 and EN 50262 standards, operable between -25 °C and +60 °C.

[View product online](#)

Description

Mini enclosure for power outlets, designed for installations in demanding industrial or commercial environments. Compatible with 18 mm modules, provides a compact and safe solution for power distribution. Includes 1 power outlet plate of 50 x 50 mm and a terminal block with capacity for 4 terminals, allowing organized and secure connections.

Technical Features

- Number of 18 mm modules per row: 4
- Total number of 18 mm modules: 4
- Number of horizontal rows: 1
- Number of openings on interface: 2
- Rated current: 63 A
- Protection degree IP: IP65
- Protection degree IK: IK09
- Fire resistance: 750 °C (IEC 60695-2-1)
- Electrical insulation class: Class II (double insulation)
- Overvoltage category: II
- Operating ambient temperature: -25...60 °C
- Housing material: Self-extinguishing polymer
- Color: Transparent green door, light gray housing (RAL 7035)

- Power dissipation: 6.5 W
- Number of PG ISO knockouts: 1
- Distribution block outputs: 2 x 10 mm², 2 x 16 mm²
- Spacing of 9 mm: 8
- Mounting: Surface
- Included accessories: 1 power outlet plate of 50 x 50 mm, 1 terminal block with 4 holes
- Locking options description: Optional lock
- Standards: IEC 670, EN 50262, IEC 60439-3
- Environmental characteristics: UV resistance, class 3 (ISO 4582:2010, ISO 4892-2:2013)
- REACH Regulation: Does not contain SVHC
- EU RoHS Directive: Proactive compliance (outside scope)
- China RoHS Regulation: Outside scope
- Mercury-free: Yes

Specifications

Insulation voltage	Clase II
Rated current (A)	63
Colour	Gris claro
EAN	3606486528815
Manufacturer	SCHNEIDER
Range	Industrial
Material	Polímero
Power (W)	6,5 w
Maximum power (W)	6,5 W
Protection	IP65

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 10 October 2026