

## Product sheet

## Kaedra Waterproof Enclosure 1x4 Modules 3 Openings 65x85 mm

Brand: SCHNEIDER

Reference: IMPO 13152M



Kaedra surface-mount waterproof enclosure with 4 modules of 18 mm in a single row, 3 openings of 65x85 mm, IP65 and IK09 protection, Class II electrical insulation, nominal current 63 A, made of self-extinguishing polymer, compliant with IEC 60439-3 and EN 50262 standards, operable between -25 °C and +60 °C.

[View product online](#)

### Description

Mini enclosure for power outlets, waterproof box type from the Kaedra range, designed for surface installations with direct mounting. Features a single row of 4 modules of 18 mm, 3 openings of 65x85 mm, and an internal depth of 61 mm. Includes 1 power outlet plate of 50x50 mm and a terminal block with capacity for 4 terminals, with outputs distributed as 2 x 10 mm<sup>2</sup> and 2 x 16 mm<sup>2</sup>. The enclosure is made of self-extinguishing polymer, with IP65 and IK09 protection, resistant to impacts and extreme environmental conditions.

### Technical Features

- Number of 18 mm modules per row: 4
- Total number of 18 mm modules: 4
- Number of horizontal rows: 1
- Number of openings on the interface: 3
- Rated current [In]: 63 A
- Power dissipation: 6.5 W
- Electrical insulation class: Class II (double insulation)
- Protection degree IP: IP65
- Protection degree IK: IK09
- Fire resistance: 750 °C (IEC 60695-2-1)

- UV resistance: Class 3 (ISO 4582:2010)
- Overvoltage category: II
- Operating ambient temperature: -25...60 °C
- Enclosure material: Self-extinguishing polymer
- Color: Transparent green door, light gray enclosure (RAL 7035)
- Mounting: Surface
- Number of PG ISO knockouts: 1
- Number of terminal blocks: 1
- Distribution block outputs: 2 x 10 mm<sup>2</sup>, 2 x 16 mm<sup>2</sup>
- Locking options description: Optional lock
- Standards: IEC 60439-3, EN 50262, IEC 670
- REACH Regulation: No SVHC
- EU RoHS Directive: Proactive compliance (out of scope)
- China RoHS: Out of scope

Specifications

|                    |               |
|--------------------|---------------|
| Insulation voltage | Clase II      |
| Rated current (A)  | 63            |
| Colour             | Gris claro    |
| EAN                | 3606486528822 |
| Manufacturer       | SCHNEIDER     |
| Long               | 61 mm         |
| Material           | Polímero      |
| Measures           | 65x85 mm      |
| # Elements         | 4             |
| Weight (kg)        | 1.5 kg        |
| Power (W)          | 6,5 w         |
| Maximum power (W)  | 6,5 W         |
| Depth              | 61 mm         |
| Protection         | IP65          |

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 10 October 2026