

Product sheet

Kaedra Distribution Box 6 Openings 12 Modules

Brand: SCHNEIDER

Reference: IMPO 13156M



Sealed Kaedra distribution box, surface mounting, with 6 openings and capacity for 12 modules of 18 mm. Designed for industrial installations, it offers double insulation (Class II), IP65 protection, and IK09 protection rating.

[View product online](#)

Description

Sealed cofret-type distribution box from the Kaedra range, designed for surface mounting with 6 openings and capacity for 12 modules of 18 mm. Ideal for electrical installations in industrial or outdoor environments, offering IP65 protection and IK09 resistance. Includes 6 power outlet plates (65 x 85 mm), 2 push-button control plates, 1 terminal block with 8 terminals, terminal block support, 2 cable bars, and 2 cable clamps.

Technical Features

- Number of 18 mm modules: 12
- Number of horizontal rows: 1
- Number of openings on interface: 6
- Rated current [In]: 63 A
- Electrical insulation class: Double insulation Class II
- Protection rating IP: IP65
- Protection rating IK: IK09
- Fire resistance: 750 °C (in accordance with IEC 60695-2-1)
- Housing material: Self-extinguishing polymer
- Operating ambient temperature: -25...60 °C
- Standards: IEC 60439-3, EN 50262, IEC 670
- Overvoltage category: II
- Power dissipation: 23 W
- Color: Transparent green door, light gray housing (RAL 7035)

- Dimensions: 340 mm (width) x 460 mm (height) x 160 mm (depth)
- Internal depth: 91 mm
- Base dimension: 91 x 100 mm
- Rail type: DIN
- Number of PG ISO knockouts: 17
- Number of terminal blocks: 1 (8 terminals)
- Distribution block outputs: 4 x 10 mm², 4 x 16 mm²
- Environmental characteristics: UV resistance, Class 3 (in accordance with ISO 4582:2010 and ISO 4892-2:2013)
- Unlocking: Optional lock
- REACH Regulation: No SVHC
- EU RoHS Directive: Proactive compliance (outside scope)
- China RoHS Regulation: Outside scope

Specifications

Insulation voltage	Clase II
High	460 mm
Rated current (A)	63
Width	340 mm
EAN	3606486528860
Manufacturer	SCHNEIDER
Range	Industrial
Material	Polímero
Power (W)	23 W
Maximum power (W)	23 W
Depth	160 mm
Protection	IP65
Cable cross-section (mm ²)	10 mm ²

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 16 October 2026