

Product sheet

Mureva waterproof box 1x12 modules 340x335 mm

Brand: SCHNEIDER

Reference: IMPO 13166M



Multipurpose housing Mureva of the Kaedra range, with 12 modules of 18 mm in a single row, surface assembly, resistant to IP65 and IK09, double insulation Class II, made of self-extinguishing polymer, with DIN support and 17 PG ISO dieboards, compatible with 63 A rated current and operation between -25 °C and +60 °C.

[View product online](#)

Description

Multipurpose housing for Mureva type power supply, designed for industrial and commercial installations. Compatible with 18 mm modules in a single row, it offers a versatile solution for electrical distribution in demanding environments. Its self-extinguishing polymer structure ensures safety in case of fire.

Technical characteristics

- Number of 18 mm modules per row: 12
- Total number of 18 mm modules: 12
- Number of horizontal rows: 1
- 9 mm steps: 24
- Nominal current [In]: 63 A
- Electrical insulation class: Double isolation Class II
- Degree of IP protection: IP65 according to Enable / Deactivate Ig
- Level of protection IK: IK09 according to H
- Fire resistance: 750 °C according to IEC 60695-2-1
- Power dissipation: 23 W
- Operating ambient temperature: -25...60 °C
- Envelope material: Self-extinguishing polymer
- Colour: Clear green door, light grey envelope (RAL 7035)
- Depth: 160 mm

- Internal depth: 91 mm
- Height: 335 mm
- Width: 340 mm
- Rail type: DIN
- Number of dies PG ISO: 17
- Description of locking options: Optional lock
- Overvoltage category: II
- Environmental characteristics: UV resistance, status 1 class 3 according to ISO 4582:2010, ultraviolet degradation test according to ISO 4892-2:2013
- Standards: Enable/disable Ig H EN 50262 IEC 670 IEC 60439-3
- EU RoHS Directive: Proactive compliance (outside the scope of EU RoHS regulations)
- RoHS China Regulations: Product outside of RoHS China
- REACH Regulation: Do not contain SVHC
- No mercury: Yes
- Information on RoHS exemptions: Yes

It adapts to industrial environments with exposure to dust, moisture and UV radiation.

Specifications

Insulation voltage	Clase II
High	335 mm
Rated current (A)	63
Width	340 mm
Colour	Gris claro
EAN	3606486528938
Manufacturer	SCHNEIDER
Range	Industrial
Long	160 mm
Material	Polímero
Measures	340x335 mm
Weight (kg)	1.5 kg
Power (W)	23 W
Maximum power (W)	23 W
Depth	160 mm
Protection	IP65

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 14 October 2026