

## Product sheet

## Mureva waterproof box 18 modules 448x460 mm

Brand: SCHNEIDER

Reference: IMPO 13168M



Multipurpose housing Mureva for power outlet, with 18 18 mm modules in one row, surface mounting, insulation class II, IP65 and IK09 resistance, made of self-extinguishing polymer, compatible with DIN rail, supports 90 A nominal current and operating temperature from -25 to 60 °C.

[View product online](#)

### Description

Multipurpose housing for food intake, type watertight chest, designed for electrical installations in demanding environments. Compatible with surface mounting, it offers a versatile solution for the management of power outputs with capacity for 18 18 mm modules in a single row. Its structure is made of self-extinguishing polymer, with fire resistance up to 750 °C and IP65 protection, ensuring sealing against dust and water.

#### Technical characteristics

- Number of 18 mm modules: 18
- Number of horizontal rows: 1
- 9 mm steps: 36
- Nominal current [In]: 90 A
- Power dissipation: 28 W
- Degree of IP protection: IP65
- Level of protection IK: IK09
- Fire resistance: 750 °C according to IEC 60695-2-1
- Electrical insulation class: Double isolation Class II
- Overvoltage category: II
- Operating ambient temperature: -25...60 °C
- Envelope material: Self-extinguishing polymer
- Colour: Clear green door, light grey envelope (RAL 7035)

- Depth: 160 mm
- Internal depth: 91 mm
- Height: 460 mm
- Width: 448 mm
- Rail type: DIN
- Number of dies PG ISO: 17
- Description of locking options: Optional lock
- Standards: IEC 60439-3, IEC 670, EN 50262
- Environmental characteristics: UV resistance, class 3 according to ISO 4582:2010 and ISO 4892-2:2013
- EU RoHS Directive: Proactive (out-of-scope) compliance
- RoHS China Regulations: Outside the scope
- REACH Regulation: No SVHC
- No mercury: Yes

This housing is suitable for industrial and outdoor applications where protection against environmental agents and high mechanical strength are required. Its transparent design allows direct display of internal components without opening the chest.

Specifications

|                    |                    |
|--------------------|--------------------|
| Insulation voltage | Clase II           |
| High               | 460 mm             |
| Width              | 448 mm             |
| EAN                | 3606486528952      |
| Manufacturer       | SCHNEIDER          |
| Range              | Industrial         |
| Material           | Polímero           |
| Measures           | 448 x 460 x 160 mm |
| Power (W)          | 28 W               |
| Depth              | 160 mm             |
| Protection         | IP65               |

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 12 October 2026