

Product sheet

Kaedra Waterproof Box 1 Row 18 Modules IP65

Brand: SCHNEIDER

Reference: IMPO 13963M



Kaedra surface mounting case, with 18 18 mm modules in a single row, IP65 and IK09 protection grade. Made of self-extinguishing polymer, it supports nominal current of 90 A, operating temperature of -25 to 60 °C and fire resistance of 750 °C.

[View product online](#)

Description

Kaedra surface watertight box, designed for electrical installations in residential environments and small shops.

Technical characteristics

- Number of 18 mm modules per row: 18
- Total number of 18 mm modules: 18
- Number of horizontal rows: 1
- Cabinet mounting: Area
- 9 mm steps: 36
- Rail type: DIN
- Number of dies PG ISO: 17
- Number of terminal blocks: 1 with clamping capacity: 16 exits
- Equipment supplied: 1 Marking kit, 1 cable clamp, 1 Terminal block support, 1 terminal block 16 holes
- Electrical insulation class: Double isolation Class II
- Nominal current [In]: 90 A
- Power dissipation: 34 W
- Degree of IP protection: IP65 according to Enable / Deactivate Ig
- Level of protection IK: IK09 according to H
- Fire resistance: 750 °C according to IEC 60695-2-1
- Environmental characteristics: UV resistance, status 1 class 3 according to ISO 4582:2010,

Ultraviolet degradation test according to ISO 4892-2:2013

- Overvoltage category: II
- Operating ambient temperature: -25...60 °C
- Envelope material: Self-extinguishing polymer
- Colour: Door, status 1 transparent green; Wrapper, status 1 light grey (RAL 7035)
- Description of locking options: Optional lock
- Standards: IEC 60439-3, IEC 670, Activate/disable Ig H, EN 50262
- REACH Regulation: Reference does not contain SVHC
- EU RoHS Directive: Proactive compliance (out-of-scope product of RoHS EU)
- No mercury: Yes
- Information on RoHS exemptions: Yes
- RoHS China Regulations: Product outside of RoHS China. Information statement on substances

Specifications

Insulation voltage	Clase II
Colour	Gris claro
EAN	3606486529065
Manufacturer	SCHNEIDER
Material	Polímero
Weight (kg)	1.5 kg
Power (W)	34 W
Maximum power (W)	34 W

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 10 October 2026