

Product sheet

Kaedra watertight box surface 2 rows 24 modules IP65

Brand: SCHNEIDER

Reference: IMPO 13964M



Kaedra surface watertight box, 2 rows, 24 modules of 18 mm, IP65, with double insulation (Class II), terminal block holder 22 holes, DIN rail mount, UV and fire resistant (750 °C), operable between -25 °C and +60 °C, self-extinguishing polymer material, optional lock.

[View product online](#)

Description

Kaedra surface watertight box, designed for electrical installations in residential environments and small shops. It has 2 rows and 24 modules of 18 mm, allowing an efficient organization of modular devices. Its structure offers IP65 and IK09 protection, ensuring resistance to dust, water and impacts. Made of self-extinguishing polymer, it resists operating temperatures between -25 °C and +60 °C and supports fire up to 750 °C. It includes a terminal block with 22 holes and accessories for mounting and arranging wiring.

Technical characteristics

- Number of horizontal rows: 2
- Total number of 18 mm modules: 24
- 9 mm steps: 24
- Number of 18 mm modules per row: 12
- Nominal current [In]: 63 A
- Electrical insulation class: Class II (Double isolation)
- Degree of IP protection: IP65 according to Enable / Deactivate Ig
- Level of protection IK: IK09 according to H
- Fire resistance: 750 °C according to IEC 60695-2-1
- Operating ambient temperature: -25...60 °C
- Overvoltage category: II
- Envelope material: Self-extinguishing polymer
- Colour: Door, status 1 transparent green; Wrapper, status 1 light grey (RAL 7035)

- Environmental characteristics: UV resistance, status 1 class 3 according to ISO 4582:2010; Ultraviolet degradation test according to ISO 4892-2:2013
- Standards: EN 50262, Activate/disable Ig, IEC 670 H, IEC 60439-3
- Rail type: DIN
- Number of dies PG ISO: 17
- Number of terminal blocks: 1 with clamping capacity: 22 exits
- Description of mounting plate: With slots
- Cabinet mounting: Area
- Accessories included: 1 terminal block 22 holes, 2 wiring bars, 2 marking kits, 1 terminal block bracket
- Equipment supplied: 2 Marking kit, 2 cable clamp, 1 Terminal block holder, 1 terminal block 22 holes
- Description of locking options: Optional lock

Specifications

Insulation voltage	Clase II
Rated current (A)	63
Colour	Gris claro
EAN	3606486529072
Manufacturer	SCHNEIDER
Long	240 mm
Material	Polímero
Measures	24 módulos de 18 mm
Protection	IP65

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 10 October 2026