

Product sheet

Kaedra Waterproof Enclosure 3 Rows 36 Modules

Brand: SCHNEIDER

Reference: IMPO 13966M



Surface-mounted waterproof Kaedra enclosure with 3 rows and 36 modules of 18 mm, made of self-extinguishing polymer. Features a terminal block with 32 holes, 16 outlets for 10 mm² cables and 16 for 16 mm², IP65 protection rating and IK09.

[View product online](#)

Description

Kaedra waterproof enclosure with surface mounting, 3 rows and 36 modules of 18 mm, designed for electrical installations in residential and small commercial environments. Made of self-extinguishing polymer, it features a reversible transparent cover for clear component identification. Includes a terminal block with 32 holes, 16 outlets for 10 mm² cables and 16 for 16 mm², plus 3 marking kits and 3 cable bars.

Technical Features

Number of horizontal rows: 3
Total number of 18 mm modules: 36
Number of 18 mm modules per row: 12
Rated current [In]: 125 A
Electrical insulation class: Class II (Double insulation)
Rail type: DIN
Number of PG ISO knockouts: 17
Number of terminal blocks: 1 with 32 terminals
Distribution block outlets: 16 x 10 mm², 16 x 16 mm²
Housing material: Self-extinguishing polymer
Protection rating IP: IP65 according to IEC 60529
Protection rating IK: IK09 according to IEC 62262
Fire resistance: 750 °C according to IEC 60695-2-1
UV resistance, class 3, status 1 according to ISO 4582:2010
UV degradation test according to ISO 4892-2:2013
Overvoltage category: II
Operating ambient temperature: -25...60 °C
Color: Door, status 1 transparent green; Housing, status 1 light grey (RAL 7035)
Mounting plate description: With slots
Cabinet mounting: Surface
Supplied equipment: 3 marking kits, 3 cable clamp, 1 terminal block support, 1 terminal block with 32 holes
Locking options description: Optional lock
Standards: IEC 60439-3, EN 50262, IEC 60529, IEC 62262, IEC 670
REACH Regulation: Reference does not contain SVH
CEU RoHS Directive: Proactive compliance (outside RoHS EU scope)
Mercury-free: Yes
RoHS exemption information: Yes
China RoHS Regulation: Product outside China RoHS scope.

Specifications

Insulation voltage	Clase II
Rated current (A)	125
Colour	Gris claro
EAN	3606486529096
Manufacturer	SCHNEIDER
Intensity	32
Material	Polímero
Protection	IP65

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 13 October 2026