

Product sheet

Kaedra Waterproof Box 3 Rows 54 Modules

Brand: SCHNEIDER

Reference: IMPO 13967M



Kaedra surface mounting housing with 3 rows and 54 18 mm modules, made of self-extinguishing polymer, IP65 and IK09 resistant, with double insulation (Class II), supports 125 A rated current and operates in ranges from -25 to 60 °C, includes 2 terminal blocks and 17 ISO PG dieboards.

[View product online](#)

Description

Kaedra surface mounting housing with 3 rows and 54 modules, designed for electrical installations in residential environments and small shops. Its self-extinguishing polymer structure offers high mechanical strength and fire protection up to 750 °C.

Technical characteristics

- Total number of 18 mm modules: 54
- Number of horizontal rows: 3
- Number of 18 mm modules per row: 18
- 9 mm steps: 36
- Nominal current [In]: 125 A
- Electrical insulation class: Class II (double isolation)
- Rail type: DIN
- Number of dies PG ISO: 17
- Number of terminal blocks: 2 with clamping capacity: 22 exits
- Envelope material: Self-extinguishing polymer
- Degree of IP protection: IP65 according to Enable / Deactivate Ig
- Level of protection IK: IK09 according to H
- Fire resistance: 750 °C according to IEC 60695-2-1
- Operating ambient temperature: -25...60 °C
- Overvoltage category: II

- Power dissipation: 65 W
- Colour: Door, status 1 transparent green; Wrapper, status 1 light grey (RAL 7035)
- Environmental characteristics: UV resistance, status 1 class 3 according to ISO 4582:2010; Ultraviolet degradation test according to ISO 4892-2:2013
- Standards: EN 50262, IEC 670, IEC 60439-3
- Unlock: Optional lock
- Accessories included: 3 marking kits, 3 cable clamps, 2 terminal blocks, 22 holes, 2 terminal block brackets
- Depth: 160 mm
- Internal depth: 88 mm
- Width: 448 mm
- Height: 610 mm
- REACH Regulation: Do not contain SVHC
- EU RoHS Directive: Proactive (out-of-scope) compliance
- RoHS China Regulations: Outside the scope
- No mercury: Yes
- Information on RoHS exemptions: Yes

Specifications

Insulation voltage	Clase II
Rated current (A)	125
Colour	Gris claro
EAN	3606486529102
Manufacturer	SCHNEIDER
Long	448 mm
Material	Polímero
Measures	448 mm x 610 mm x 160 mm
Weight (kg)	1.5 kg
Power (W)	65 W
Maximum power (W)	65 W
Depth	160 mm

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 12 October 2026