

Product sheet

Kaedra Waterproof Enclosure 448 x 610 mm 36 Modules

Brand: SCHNEIDER

Reference: IMPO 13972M



Kaedra waterproof enclosure, modular design with 36 modules of 18 mm distributed in 3 rows, surface mounting, housing in self-extinguishing polymer with IP65 and IK09 protection. Includes 1 terminal block with 32 terminals, 4 push button plates, and 1 power output plate 65 x 85 mm.

[View product online](#)

Description

Multipurpose Kaedra enclosure of 448 x 610 mm with 36 modules and 4 openings, designed for modular installations in residential and small commercial environments. Its structure in self-extinguishing polymer offers high mechanical resistance and IP65 protection, with IK09 protection level and fire resistance up to 750 °C.

Technical Features

- Electrical insulation class: Class II (double insulation)
- Total number of 18 mm modules: 36
- Number of horizontal rows: 3
- Modules per row: 12
- 9 mm steps: 24
- Rated current: 125 A
- Rail type: DIN
- Number of PG ISO knockouts: 17
- Number of terminal blocks: 1 with clamping capacity: 32 terminals
- Distribution block outputs: 16 x 10 mm², 16 x 16 mm²
- Number of openings in interface: 4
- Housing material: Self-extinguishing polymer
- Protection rating IP: IP65 according to IEC 60529
- Impact protection rating IK: IK09 according to IEC 62262

- Fire resistance: 750 °C according to IEC 60695-2-1
- UV resistance: Class 3, Grade 1 according to ISO 4582:2010
- UV degradation test: according to ISO 4892-2:2013
- Overvoltage category: II
- Operating ambient temperature: -25...60 °C
- Color: Door, Grade 1 transparent green; Housing, Grade 1 light gray (RAL 7035)
- Cabinet mounting: Surface
- Faceplate type: Reversible transparent
- Locking options description: Optional lock
- Standards: IEC 60439-3, IEC 670, EN 50262
- REACH Regulation: No SVHC content
- EU RoHS Directive: Proactive compliance (outside scope)
- China RoHS Regulation: Outside scope
- Mercury-free: Yes
- RoHS exemption information: Yes

Specifications

Insulation voltage	Clase II
High	448 mm
Rated current (A)	125
Width	610 mm
Colour	Gris claro
EAN	3606486529140
Manufacturer	SCHNEIDER
Intensity	36
Material	Polímero
Measures	448 x 610 mm
Protection	IP65

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 12 October 2026