

## Product sheet

## Daily analog time switch 1 channel 16 A 50 Hz

Brand: SCHNEIDER

Reference: IMPO 15335



1 channel, 16 A analog daily time switch, with manual time adjustment and accuracy of  $\pm 1$  s/day at 20 °C. Designed for building applications, it supports loads up to 16 A in 230 V AC, with a 24 h cycle and a minimum interval of 15 min.

[View product online](#)

### Description

Analogue daily time switch of the Acti9 range, designed for manual switching of charge in electrical installations of buildings. Ideal for controlling lighting or equipment with fixed hours, with a 24-hour cycle and manual hour adjustment. Its compact design and DIN rail mounting makes it suitable for electrical cabinet installations.

#### Technical characteristics

- Number of channels: 1
- Cycle duration: 24 h
- Maximum number of switches: 48 activated - 48 disabled
- Minimum interval duration: 15 min
- Adjustment type: Manual hour change
- Measurement accuracy:  $\pm 1$  s/day at 20 °C
- Power consumption: 0.5 W
- Maximum switching intensity: 16 A - 250 V AC pf = 1/4 A - 250 V AC pf = 0.6
- Nominal employment voltage: 230 V AC at 50 Hz
- Mounting bracket: Rail DIN
- 9 mm steps: 2
- Colour tone: White - cable type: RAL 9003
- Connections: Screw terminals
- Dimensions: 18 mm (width) x 90 mm (height) x 66 mm (depth)
- Weight: 0.097 kg

- Operating ambient temperature: -25...50 °C
- Degree of IP protection: Terminals, status 1 IP20 B
- Market segment: Residential, small shops
- EU RoHS Directive: As per
- No mercury: Yes
- Sustainable supply status: Product Green Premium

It is used in lighting installations in buildings, especially for fluorescent, halogen, incandescent, fluorcompact and LED lamps, with loads up to 300 W. Its manual operation allows to adjust on and off according to daily needs.

Specifications

|                     |                                                      |
|---------------------|------------------------------------------------------|
| Frequency           | 50 Hz                                                |
| Rated current (A)   | 16                                                   |
| EAN                 | 3303430153351                                        |
| Manufacturer        | SCHNEIDER                                            |
| Long                | 90 mm                                                |
| Halogen-free        | Yes                                                  |
| Measures            | 18 mm (ancho) x 90 mm (altura) x 66 mm (profundidad) |
| # Elements          | 1                                                    |
| Weight (kg)         | 0,097 kg                                             |
| Power (W)           | 0,5 W                                                |
| Maximum power (W)   | 300 W                                                |
| Depth               | 66 mm                                                |
| Protection          | IP20                                                 |
| Nominal voltage (V) | 230 V                                                |
| Current type        | AC                                                   |
| Engine              | AC                                                   |

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 10 October 2026