

Product sheet

Surge Protector 3P+N Type 1+2

Brand: SCHNEIDER

Reference: IMPO 16332



Surge protector type 1+2 with MOV technology for electrical installations of 230/400 V AC, 50/60 Hz, with common mode protection (100 kA) and differential mode protection (25 kA), protection level <1.5 kV, response time ≤ 25 ns, DIN rail mounting, 3P+N, compatible with gG fuse 315 A or Compact NSX100B circuit breaker, suitable for small businesses.

[View product online](#)

Description

Surge protector type 1+2 with MOV technology and plug-in cartridge, designed to protect electrical installations in small businesses. Compatible with TN-S and TT earthing systems, provides common mode and differential mode protection through inter-electrode distance. Application recommended for currents above 0.1 A.

Technical Features

- Number of poles: 3P + N
- Rated operating voltage: 230/400 V AC ($\pm 10\%$) at 50/60 Hz
- Rated discharge current: Common mode 100 kA (N/PE), differential mode 25 kA (L/N)
- Impulse current: Common mode 100 kA (N/PE) 50 A·s, differential mode 25 kA (L/N) 12.5 A·s
- Maximum continuous operating voltage: 350 V (L/N and N/PE)
- Protection level: <1.5 kV (type 2, L/N)
- Current monitoring: 25 kA (differential mode L/N), 0.1 kA (common mode N/PE)
- Remote signaling: 1 SD (1 C/O)
- Response time: ≤ 25 ns
- Connections: Tunnel terminals (2.5...35 mm²), tightening torque 4.5 N·m
- Surge current: 25 kA
- Protection degree IP: IP40 (front face, state 1), IP20 (installed, state 1)
- Impact protection degree IK: IK05 (in accordance with insulation accessory)
- Operating ambient temperature: -25...60 °C
- Storage ambient temperature: -40...80 °C

- Maximum operating altitude: 2000 m
- Relative humidity: 5...90 %
- Material: PBT (polybutylene terephthalate)
- Color: Anthracite grey (RAL 7016)
- Weight: 1.43 kg
- Height: 90 mm
- Width: 142.8 mm
- Depth: 70 mm
- Mounting support: DIN rail
- Mounting type: Adjustable clip
- Step size: 9 mm, 16 steps
- Standards: EN 61643-11:2012, IEC 61643-11:2011
- Certifications: CE, KEMA-KEUR

Specifications

Frequency	50/60 Hz
High	90 mm
Rated current (A)	400
Width	142,8 mm
Colour	Gris antracita
EAN	3606480060427
Manufacturer	SCHNEIDER
Intensity	25
Long	90 mm
Measures	90 mm x 142,8 mm x 70 mm
# Elements	1
No. of poles	3P+N
Weight (kg)	1,43 kg
Depth	70 mm
Protection	IP40
Cable cross-section (mm ²)	35 mm ²
Nominal voltage (V)	230/400 V AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 10 October 2026