

## Product sheet

# Acti9 NG125L 2P 50 A D Curve Automatic Circuit Breaker

Brand: SCHNEIDER

Reference: IMPO 18845



Miniature automatic circuit breaker Acti9 NG125L, 2 poles, 50 A, D curve, with breaking capacity Icu of 50 kA at 380-415 V AC, thermal-magnetic design, 35 mm DIN rail mounting, suitable for installations in small buildings and small businesses, with position indicator and integrated lock.

[View product online](#)

## Description

Miniature automatic circuit breaker from the Acti9 NG125 range, designed to protect electrical circuits in installations in small buildings and small businesses. Offers thermal and magnetic protection with D curve, suitable for loads with high inrush current peaks.

## Specifications

|                                        |                                                                                                                    |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Frequency                              | 50/60 Hz                                                                                                           |
| Rated current (A)                      | 50                                                                                                                 |
| Width                                  | 5,4 cm                                                                                                             |
| Curve                                  | D                                                                                                                  |
| EAN                                    | 3303430188452                                                                                                      |
| Manufacturer                           | SCHNEIDER                                                                                                          |
| Long                                   | 10,3 cm                                                                                                            |
| No. of poles                           | 2P                                                                                                                 |
| Weight (kg)                            | 0,48                                                                                                               |
| Depth                                  | 8,1 cm                                                                                                             |
| Protection                             | IP20                                                                                                               |
| Cable cross-section (mm <sup>2</sup> ) | 35                                                                                                                 |
| Rated voltage                          | 250                                                                                                                |
| Nominal voltage (V)                    | 220...240 V AC 50/60 Hz, 380...415 V AC 50/60 Hz, 440 V AC 50/60 Hz, 500 V AC 50/60 Hz, ≤ 250 V corriente continua |

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 13 October 2026