

Product sheet

Magnetotérmico, Acti9 NG125L, 3P, 63 A, D curva, 50 kA (IEC 60947-2)

Brand: SCHNEIDER

Reference: IMPO 18855



Miniature circuit breaker 3P, 63 A, curve D, with breaking capacity Icu of 50 kA at 380–415 V AC, thermal-magnetic technology, DIN 35 mm rail mounting, suitable for installations in small businesses and buildings, with position indicator and integrated lock for operational safety.

[View product online](#)

Description

Miniature circuit breaker 3P with curve D and thermal-magnetic technology, designed to protect electrical circuits in installations for small businesses and buildings. Offers a breaking capacity Icu of 50 kA at 380–415 V AC, operating on AC networks at 50/60 Hz and nominal operating voltage up to 500 V AC.

Specifications

Frequency	50/60 Hz
Rated current (A)	63
Width	81 mm
Curve	D
EAN	3303430188551
Manufacturer	SCHNEIDER
Long	103 mm
Measures	103 mm x 81 mm x 81 mm
No. of poles	3P
Weight (kg)	0,72 kg
Depth	81 mm
Protection	IP20
Nominal voltage (V)	500 V
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 10 October 2026