Product sheet

Magnetotérmico, Acti9 NG125L, 4P, 10 A, D curva, 50 kA (IEC 60947-2)

Brand: SCHNEIDER

Reference: IMPO 18857



Miniature circuit breaker Acti9 NG125L, 4 poles, 10 A, curve D, with breaking capacity Icu of 50 kA at 380-415 V AC, thermal-magnetic design, DIN 35 mm rail mounting, IP20 protected, suitable for installations in small buildings and small businesses, with position indicator and integrated lock.

View product online

Description

Miniature circuit breaker from the Acti9 NG125 range, designed for protection of electrical circuits in small building and small commercial installations. Offers thermal and magnetic protection with curve D, suitable for loads with high inrush currents.

Specifications

Frequency	50/60 Hz
Rated current (A)	10
Width	108 mm
Curve	D
EAN	3303430188575
Manufacturer	SCHNEIDER
Measures	103 mm x 108 mm x 81 mm
No. of poles	4P
Weight (kg)	0,96 kg
Depth	81 mm
Protection	IP20
Cable cross-section (mm²)	35 mm²
Nominal voltage (V)	220...240 V AC 50/60 Hz, 380...415 V AC 50/60 Hz, 440 V AC 50/60 Hz, 500 V AC 50/60 Hz

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 25 November 2026