

Product sheet

Minimum voltage coil MNx 220-240 V AC

Brand: SCHNEIDER

Reference: IMPO 19061



Minimum voltage coil MNx for electrical installations in industrial and commercial environments. Operates with control voltage 220...240 V AC 50/60 Hz, compatible with NG125 range. Fixed mounting on 35 mm DIN rail, with IP20 B and IP4 protection degree.

[View product online](#)

Description

Minimum voltage coil MNx designed to operate in control circuits with voltages of 220...240 V AC 50/60 Hz.

Technical characteristics

- Control circuit voltage: 220...240 V AC 50/60 Hz
- Control type: Standard
- Step distance: 9 mm
- Rated insulation voltage: 690 V AC 50/60 Hz (in accordance with EN/IEC 60947-5-1)
- Surge voltage withstand: 8 kV (in accordance with EN/IEC 60947-5-1)
- Protection degree IP: IP20 B and IP4 (in accordance with EN/IEC 60947-5-1)
- Contamination degree: 3 (in accordance with EN/IEC 60947-5-1)
- Overvoltage category: II
- Tropicalization: 2 (in accordance with EN/IEC 60947-5-1)
- Relative humidity: 95 % at 55 °C
- Operating ambient temperature: -25...60 °C
- Storage ambient temperature: -40...85 °C
- Electrical durability: 10000 cycles (in accordance with EN/IEC 60947-5-1)
- Connections: Plate terminal for 1 rigid cable 0,5...2,5 mm², 1 flexible cable 0,5...1,5 mm², 1 flexible cable 0,5...1,5 mm² with terminal, 2 flexible cables 2,5 mm², 2 rigid cables 2,5 mm², 2 flexible cables 1,5 mm² with terminal
- Stripping length for terminal connection: 10 mm

- Torque: 1 N·m
- Product weight: 0,199 kg
- Standards: EN/IEC 60947-5-1
- Certifications: ASEFA, KEMA, LCIE, ASTA
- Compliant with REACH without SVHC: Yes
- EU RoHS Directive: Compliant
- Free of toxic heavy metals: Yes
- Mercury-free: Yes
- RoHS exemption information: Yes
- China RoHS regulation: Proactive China RoHS declaration (outside legal scope of China RoHS)
- WEEE: In the European Union market, the product must be disposed of through specific waste collection systems

Specifications

Frequency	50/60 Hz
EAN	3303430190615
Manufacturer	SCHNEIDER
Range	Industrial
Long	35 mm
Measures	10 mm
Weight (kg)	0,199 kg
Depth	35 mm
Protection	IP20
Cable cross-section (mm²)	2,5 mm²
Nominal voltage (V)	220...240 V
Current type	AC
Engine	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 14 October 2026