

Product sheet

Vigi Block 3P 125 A 30 mA

Brand: SCHNEIDER

Reference: IMPO 19106



Vigi Block NG125 3P with nominal current of 125 A, operating voltage 230–415 V AC, 50/60 Hz, adjustable earth leakage sensitivity to 300, 500, 1000 and 3000 mA, adjustable instantaneous, selective or delayed protection, independent voltage trip technology, protection degree IP40, mounting on 35 mm DIN rail, compatible with tunnel-type terminals for flexible cables 10–50 mm² and rigid cables 16–70 mm².

[View product online](#)

Description

Vigi Block NG125 3P with nominal current of 125 A, designed for earth leakage protection in three-phase electrical installations. Installed at the system output, it offers adjustable earth leakage sensitivity of 300, 500, 1000 and 3000 mA, with options for adjustable instantaneous, selective or delayed protection.

Specifications

Frequency	50/60 Hz
Rated current (A)	125
Width	180 mm
Class	AC
EAN	3303430191063
Manufacturer	SCHNEIDER
Long	118 mm
No. of poles	3P
Weight (kg)	0,75 kg
Depth	81 mm
Protection	IP40
Nominal voltage (V)	230...415 V AC
Current type	AC

may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 9 October 2026