

Product sheet

3P Isolating Switch Interpact INS125

Brand: SCHNEIDER

Reference: IMPO 28910



ComPact range 3P section switch, designed for industrial applications with 125 A rated current, 750 V AC insulation voltage and 8 kV voltage peak resistance. Supports up to 154 kA of short-circuit capacity with automatic upstream switch, with 15,000-cycle mechanical durability and IP40 protection.

[View product online](#)

Description

ComPact range 3P section switch, designed for the safe disconnection of electrical circuits in industrial and commercial installations. Its fixed construction and DIN rail mounting allow direct integration into electrical enclosures.

Specifications

Frequency	50/60 Hz
Rated current (A)	125
Width	135 mm
Colour	Black
EAN	3303430289104
Manufacturer	SCHNEIDER
Range	Industrial
Long	100 mm
Measures	100 mm x 135 mm x 62,5 mm
# Elements	3
No. of poles	3P
Weight (kg)	0,8 kg
Depth	62,5 mm
Protection	IP40
Cable cross-section (mm ²)	30
Nominal voltage (V)	690
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 11 October 2026