

Product sheet

3P Isolating Switch Black 250 A

Brand: SCHNEIDER

Reference: IMPO 31166



3P isolating switch from the ComPact range, designed for AC 50/60 Hz circuits and direct current up to 250 V. Supports a nominal current of 250 A, insulation voltage of 750 V AC, and a short-circuit breaking capacity of 30 kA. Features visible disconnection, position indicator, and fixed mounting on DIN rail.

[View product online](#)

Description

3P isolating switch from the ComPact range, designed for the safe disconnection of electrical circuits in industrial installations. Compatible with AC and direct current networks, it provides visible disconnection and a contact position indicator to ensure safety during maintenance operations.

Specifications

Frequency	50/60 Hz
High	136 mm
Rated current (A)	250
Width	140 mm
Colour	Black
EAN	3303430311669
Manufacturer	SCHNEIDER
Range	Industrial
Long	136 mm
Measures	136 mm x 140 mm x 96 mm
# Elements	3
No. of poles	3P
Weight (kg)	2 kg
Depth	96 mm
Protection	IP40
Nominal voltage (V)	690 V
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 10 October 2026