

Product sheet

Fixed trip coil MX 24-30 VAC/DC

Brand: SCHNEIDER

Reference: IMPO 33659



Liber deseng deriv shooting coil for fixed automatic switches of the Masterpact NT, NW and Compact NS630b ranges...3200. Works with 24 V AC control voltage 50 Hz or 24...30 V DC. Shot threshold between 0.7 and 1.1 times the nominal voltage. Maintenance power of 4.5 VA.

[View product online](#)**Description**

MX firing coil for fixed switches of the range Masterpact NT, Masterpact NW, Compact NS630b...1600 and Compact NS1600b...3200. Designed for control applications, it allows the operation of the switch under control circuit voltages of 24 V AC 50 Hz or between 24 and 30 V DC. Its coil type is Liber deseng deriv, with trigger voltage threshold between 0.7 and 1.1 times the nominal value.

Technical characteristics

- Control circuit voltage: 24 V AC 50 Hz, 24...30 V DC
- Threshold of firing voltage: 0.7...1.1 x One
- Maintenance power supply: 4.5 VA
- Type of assembly: Fixed
- Response time: 50 ms (Compact NS630b...1600), 55 ms (Compact NS1600b...3200), 70 ms (Masterpact NT), 70 ms (Masterpact NW)
- Type of shot coil: Liber deseng deriv
- Compatibility: Masterpact NT, Masterpact NW, Compact NS630b...1600, Compact NS1600b...3200
- REACH Regulation: Contains SVHC over the threshold
- EU RoHS Directive: Proactive (out-of-scope) compliance
- RoHS exemptions: Yes
- RoHS China Regulations: Outside the scope
- No mercury: Yes

Specifications

Frequency	50 Hz
EAN	3303430336594
Manufacturer	SCHNEIDER
Nominal voltage (V)	24 V CA 50 Hz, 24...30 V DC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 15 October 2026