

Product sheet

Surface Mount 125 A 3P+N+E IP67

Brand: SCHNEIDER

Reference: IMPO 81195



Surface mount connector 125 A, 3P+N+E, 380-415 V AC, IP67, flush wall mounting, with captive screws, cable section 16-70 mm², thread Pg 48, IK08 protection rating, made of self-extinguishing polymer with stainless steel and nickel-plated brass contacts, designed for industrial environments in small businesses.

[View product online](#)

Description

Surface mount 125 A 3-pole +NT, 380-415 V IP67, designed for industrial applications in demanding environments. Ideal for connections in small businesses and environments with high levels of contamination or humidity, ensuring a safe and durable connection.

Technical Features

- Number of poles: 3P+N+E
- Power supply type: AC
- Output standard: Industrial
- Rated operating voltage: 380...415 V
- Rated current: 125 A
- Supply frequency: 50/60 Hz
- Earth terminal position clockwise: 6 h
- Housing material: Engineering self-extinguishing polymer
- Contact material: Stainless steel pins and springs, nickel-plated brass sleeves
- Connections: Captive screws, fully loosened
- Cable section: 16...70 mm²
- Cable entry: Cable gland
- Thread type: Pg 48
- Protection rating IP: IP67 according to IEC 60529
- IK protection rating: IK08 according to EN 62262

- Fire resistance: 850 °C according to IEC 60695-2-11
- Operating ambient temperature: 35 °C (86400 s)
- Relative humidity: 50 % at 40 °C, 70 % at 30 °C, 90 % at 20 °C
- Product weight: 2.4 kg
- Base dimension: 114 x 224 mm
- Height: 340 mm
- Width: 114 mm
- Depth: 213 mm
- Color: Grey (RAL 7035)
- Voltage color code: Red
- Standards: EN 60309-1, EN 60309-2
- Market segment: Small businesses
- Compatibility code: Pratika connector
- Sustainable offering status: Green Premium product
- REACH Regulation: Contains SVHC above threshold
- EU RoHS Directive: Proactive compliance (outside scope)
- China RoHS Regulation: Outside scope
- Mercury-free: Yes
- RoHS exemptions information: Yes

Specifications

Frequency	50/60 Hz
Rated current (A)	125
Width	114 mm
Colour	Grey
EAN	3303430811954
Manufacturer	SCHNEIDER
Range	Industrial
Long	340 mm
Material	Polímero
No. of poles	3P+N+E
Weight (kg)	2,4 kg
Depth	213 mm
Protection	IP67 - uso externo
Cable cross-section (mm²)	16
Nominal voltage (V)	380...415 V
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 9 October 2026