

Product sheet

Industrial Socket 125 A 3P+N+E IP67

Brand: SCHNEIDER

Reference: IMPO 81695



Industrial socket 3P+N+E, 125 A, 380-415 V AC, panel mounting, IP67 protection rating and IK08. Made of self-extinguishing polymer, contacts in stainless steel and nickel-plated brass. Compatible with EN 60309 standard, suitable for demanding industrial environments, resistant to temperatures up to 850 °C and relative humidity up to 90 %.

[View product online](#)

Description

Industrial socket type PratiKa, panel-mounted, designed for low-voltage applications in industrial environments. Compatible with international standards, provides safe and durable connection for electrical installations in demanding conditions.

Technical Features

- Number of poles: 3P + N + E
- Rated operating voltage: 380...415 V AC
- Rated current: 125 A
- Supply frequency: 50/60 Hz
- Earth terminal position clockwise: 6 o'clock
- Housing material: Engineering self-extinguishing polymer
- Contact material: Stainless steel pins and springs, nickel-plated brass sleeves
- Connections: Captive screws, fully loosened
- Wire cross-section supported: 16...70 mm²
- Protection rating IP: IP67
- Protection rating IK: IK08
- Fire resistance: 850 °C
- Operating ambient temperature: 35 °C
- Standards: EN 60309-1, EN 60309-2

- Weight: 1.346 kg
- Dimensions: 110 x 114 x 161 mm (width x height x depth)
- Color: Grey (RAL 7035)
- Voltage color code: Red
- Sustainable offering status: Green Premium product
- Contains SVHC above threshold (REACH)
- Product outside the scope of EU RoHS and China RoHS

Specifications

Frequency	50/60 Hz
Rated current (A)	125
Width	114
Colour	Grey
EAN	3303430816959
Manufacturer	SCHNEIDER
Range	Industrial
Long	110
Material	Polímero
No. of poles	3P+N+E
Weight (kg)	1,346
Depth	16,1 cm
Protection	IP67 - uso externo
Cable cross-section (mm²)	16
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 12 October 2026