

Product sheet

Wall Mount Plug 32 A 3P+N+E 90° IP67

Brand: SCHNEIDER

Reference: IMPO 83871



Panel-mount plug, 32 A, 3P+N+E, 380-415 V AC, 50-60 Hz, with IP67 and IK08 protection rating. Designed for industrial environments, made of self-extinguishing engineering polymer, with nickel-plated brass contacts and non-loosening screw terminals. Compatible with PratiKa system, suitable for installations in small businesses and demanding environments.

[View product online](#)

Description

Wall mount plug 32 A 3P+N+E 380-415 V IP67 50-60 Hz designed for industrial applications in demanding environments.

Technical features

- Number of poles: 3P+N+E
- Rated current: 32 A
- Rated operating voltage: 380...415 V
- Supply frequency: 50/60 Hz
- Earth terminal position clockwise: 6 o'clock
- Socket and plug material: Self-extinguishing engineering polymer
- Contact material: Pins, class 1 nickel-plated brass
- Connections - terminals: Non-loosening screws
- Cable cross-section: 2.5...10 mm²
- Protection rating IP: IP67 according to IEC 60529
- Protection rating IK: IK08 according to EN 62262
- Fire resistance: 850 °C according to IEC 60695-2-1
- Operating ambient temperature: -25...40 °C
- Maximum operating altitude: 2000 m
- Relative humidity: 50 % at 40 °C, 70 % at 30 °C, 90 % at 20 °C

- Product weight: 0.333 kg
- Base dimension: 91 x 100 mm
- Height: 159 mm
- Width: 90 mm
- Depth: 115 mm
- Color: Gray - cable type: RAL 7035
- Voltage color code: Red
- Standards: EN 60309-1, EN 60309-2
- Market segment: Small businesses
- Compatibility code: PratiKa plug
- Sustainable offering status: Green Premium product
- REACH Regulation: Reference contains SVHC above threshold
- EU RoHS Directive: Proactive compliance (product outside RoHS EU scope)
- Mercury-free: Yes
- RoHS exemptions information: Yes
- China RoHS regulation: Product outside China RoHS scope. Substance information declaration

Specifications

Frequency	50/60 Hz
Rated current (A)	32
Width	90 mm
Colour	Grey
EAN	3303430838715
Manufacturer	SCHNEIDER
Range	Industrial
Material	Polímero
No. of poles	3P+N+E
Weight (kg)	0,333 kg
Depth	115 mm
Protection	IP67 - uso externo
Cable cross-section (mm²)	10 mm²
Nominal voltage (V)	380-415 V
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 11 October 2026