

Product sheet

Dardo Plus 4P 125A 30 mA Instantaneous RCD Module

Brand: SCHNEIDER

Reference: IMPO A9N18554



4P Dardo Plus RCD module with nominal current of 125 A, earth leakage sensitivity of 30 mA, and instantaneous response. Designed for small commercial installations, operates on AC 50 Hz networks with a nominal operating voltage of 400...415 V.

[View product online](#)

Description

Dardo Plus RCD module designed to protect electrical installations in small commercial environments.

Technical Features

- Number of poles: 4P
- Rated current [In]: 125 A
- Network type: AC
- Earth leakage sensitivity: 30 mA
- Protection delay: Instantaneous
- Protection class: Type A-SI
- System location: Output
- Network frequency: 50 Hz
- Nominal operating voltage [Ue]: 400...415 V AC 50 Hz
- Tripping technology: Voltage-independent
- Rated insulation voltage [Ui]: 500 V AC 50/60 Hz according to EN > 40 A
- Impulse withstand voltage [Uimp]: 6 kV according to EN > 50 A
- Mounting type: Clip-adjustable
- Mounting support: Symmetrical 35 mm DIN rail
- Electrical connection to MCB: By screws
- Spacing: 9 mm
- Height: 95 mm
- Width: 198 mm

- Depth: 73 mm
- Weight: 0.58 kg
- Color: White
- Mechanical durability: 20000 cycles
- Connections - terminals: Tunnel-type terminals 1...35 mm² flexible, 1...50 mm² rigid
- Stripping length: 15 mm
- Tightening torque: 3.5 N·m
- Compatibility: Terminal
- Standards: EN 61009
- Protection degree IP: IP20
- Contamination degree: 3 according to EN > 50 A
- Operating ambient temperature: -25...60 °C
- Storage ambient temperature: -40...60 °C
- REACH Regulation: Does not contain SVHC
- EU RoHS Directive: Compliant
- Mercury-free: Yes
- RoHS Exemptions: Yes
- China RoHS Regulation: Product outside the scope of China RoHS
- WEEE: Must be disposed of according to specific system in the EU

Specifications

Frequency	50 Hz
Rated current (A)	125
Colour	White
Sensitivity	30 mA
EAN	3606480376573
Manufacturer	SCHNEIDER
No. of poles	4P
Weight (kg)	0,58 kg
Depth	73 mm
Protection	IP20
Nominal voltage (V)	400...415 V
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 11 October 2026