

Product sheet

Adjustable Clip-On 4P 125A 300mA Vigi Block

Brand: SCHNEIDER

Reference: IMPO A9N18555



4P Vigi block with nominal current of 125 A, earth leakage sensitivity of 300 mA, type A-SI, for AC 50 Hz installations. Operating voltage 230...415 V AC, with voltage-independent tripping technology. Mounting on 35 mm DIN rail, connection via screws, resistance to voltage surges of 6 kV.

[View product online](#)

Description

4P Vigi C120 block with nominal current of 125 A, designed to protect electrical installations in small commercial environments. Its voltage-independent tripping technology ensures immediate response to residual current leakage, guaranteeing safety under AC 50 Hz grid conditions.

Technical Features

- Number of poles: 4P
- Rated current [In]: 125 A
- Network type: AC
- Earth leakage sensitivity: 300 mA
- Protection delay: Instantaneous
- Protection class: Type A-SI
- Rated operating voltage [Ue]: 230...415 V AC 50 Hz
- Rated insulation voltage [Ui]: 500 V AC 50/60 Hz in accordance with EN > 40 A
- Impulse withstand voltage [Uimp]: 6 kV in accordance with EN > 50 A
- System location: Output
- Grid frequency: 50 Hz
- Tripping technology: Voltage-independent
- Mounting support: Symmetrical 35 mm DIN rail
- Mounting type: Adjustable clip-on
- Electrical connection to MCB: Via screws

- Terminals: Tunnel type 1...35 mm² flexible, 1...50 mm² rigid
- Stripped cable length: 15 mm
- Tightening torque: 3.5 N·m
- Height: 95 mm
- Width: 198 mm
- Depth: 73 mm
- Weight: 0.58 kg
- Color: White
- Mechanical durability: 20000 cycles
- Protection degree IP: IP20
- Contamination degree: 3 in accordance with EN > 50 A
- Operating ambient temperature: -25...60 °C
- Storage ambient temperature: -40...60 °C
- Standards: EN 61009
- Compatibility: Terminal
- Market segment: Small businesses
- REACH Regulation: Does not contain SVHC
- EU RoHS Directive: Compliant
- RoHS Exemptions: Yes
- China RoHS: Product outside scope
- WEEE: Must be disposed of via specific systems in the EU

Specifications

Frequency	50 Hz
Rated current (A)	125
Width	198 mm
Colour	White
Sensitivity	300 mA
EAN	3606480376580
Manufacturer	SCHNEIDER
Long	95 mm
No. of poles	4P
Weight (kg)	0,58 kg
Depth	73 mm
Protection	IP20
Cable cross-section (mm ²)	35 mm ²
Nominal voltage (V)	230...415 V AC
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 18 October 2026