

Product sheet

64-channel discrete input module 24 V DC

Brand: SCHNEIDER

Reference: IMPO BMXDDI6402K



Discreet 64-channel isolated input module for Modicon X80 systems, compatible with 24 V DC positive, inlet impedance of 40 k Ω , typical filtering time of 4 ms and maximum 7 ms. Designed for industrial environments with IP20 protection, 3 gn vibration resistance and 30 gn shocks.

[View product online](#)

Description

64-channel discrete inlet module designed for Modicon X80 systems. It allows the connection of digital signals in industrial environments, offering electrical insulation to reduce electromagnetic interference. It works with a positive input voltage of 24 V DC and has an input impedance of 40 k Ω .

Technical characteristics

- Number of digital entries: 64
- Discreet input: Isolated
- Type of entry: Current collector (positive logic)
- Input voltage: 24 V DC positive
- Discreet input current: 0.6 mA
- Tensions range: 19...30 V
- Entry Impedance: 40000 Ohm
- Insulation resistance: > 10 MOhm at 500 V DC
- Dissipated power: 4.3 W
- Typical filter time: 4 ms
- Maximum filter time: 7 ms
- Parallel entries: No
- Typical current consumption: 160 mA in 3.3 V DC
- MTBF: 342216 h
- Protection type: 1 external fuse per channel group, 0.5 A, fast cast, no reverse polarity

protection

- Detection threshold voltage: > 18 V DC
- Status LED: RUN (green), channel diagnosis (green), module error (red), module I/O (red)
- Weight: 0.145 kg
- Degree of protection: IP20
- Dielectric force: 1500 V AC (50/60 Hz) for 1 minute between primary/secondary, 500 V DC for 1 minute between groups of channels
- Vibration resistance: 3 gn
- Shock resistance: 30 gn
- Storage ambient temperature: -40...85 °C
- Operating ambient temperature: 0...60 °C
- Relative humidity: 5...95 % at 55 °C without condensation
- Maximum operating altitude: 0...2000 m, 2000..5000 m with
- Directives: 2014/35/EU (low voltage), 2014/30/EU (EMC)
- Sustainable supply status: Product Green Premium
- According to REACH without SVCC: Yes
- EU RoHS Directive: Proactive (out-of-scope) compliance
- No mercury: Yes
- RoHS exemptions: Yes
- RoHS China Regulations: X
- WEEE: To be discarded according to specific EU collection system

Specifications

Frequency	50/60 Hz
EAN	3595863910445
Manufacturer	SCHNEIDER
Range	Industrial
Intensity	160
Weight (kg)	0,145 kg
Power (W)	4,3 W
Maximum power (W)	4,3 W
Protection	IP20
Nominal voltage (V)	24 V CC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 9 October 2026