

Product sheet

64-Channel Discrete Output Module 24 V DC

Brand: SCHNEIDER

Reference: IMPO BMXDDO6402K



64-channel discrete output module with solid-state technology, positive logic, output voltage 24 V DC (19-30 V DC), current per channel 0.1 A, response time 1.2 ms, insulation resistance > 10 MΩ at 500 V DC, compatible with EN/IEC 61131-2, integrated protection against short circuits, overloads, and overvoltages, IP20 protection rating, operable in industrial environments from -40 to 60 °C.

[View product online](#)

Description

64-channel discrete output module, solid-state type, positive logic, designed for industrial automation systems compliant with EN/IEC 61131-2. Operates at output voltage of 24 V DC (19-30 V DC), output current per channel 0.1 A, response time 1.2 ms. Features integrated protection against short circuits, overloads, overvoltages, and reverse polarity. Suitable for industrial environments with operating temperatures from 0 to 60 °C and storage temperatures from -40 to 85 °C.

Specifications

High	1,2 ms
EAN	3595863910490
Manufacturer	SCHNEIDER
Range	Industrial
Length	1
Weight (kg)	0,15 kg
Power (W)	6,85 W
Protection	IP20
Nominal voltage (V)	24 V CC

may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 10 October 2026