

Product sheet

Standard RS232/485 serial connection module

Brand: SCHNEIDER

Reference: IMPO BMXNOM0200



Series communication module for the Modicon X80 range, with two integrated interfaces: RS232 (115.2 kbit/s, 8 threads) and RS485 (57.6 kbit/s, 1 pair braided). Internal power supply from rack, consumption of 80 mA to 24 V DC.

[View product online](#)

Description

Serial communication module for Modicon X80 systems, designed to connect devices using RS232 and RS485 interfaces. It allows the transmission of data through integrated serial connections, facilitating integration into industrial environments.

Technical characteristics

- Product range: Modicon X80
- Type of product or component: Module of leagues em serie
- Concept: Ligação de serie
- Integrated connection type: RS232 RJ45 115.2 kbit/s 8 fios, RS485 RJ45 57.6 kbit/s 1 pair braided
- Protection treatment: TC
- Power supply: Source of internal feeding via rack
- Marked: EC
- Local markings: Module Falha (ERR), 1 red LED status; Module Execução (RUN), 1 green LED status; Atividade na ligação de serie (SER COM 0), 1 green LED status; Atividade na ligação de serie (SER COM 1), 1 green LED status
- Current consumption: 80 mA in 24 V DC
- Module format: Standard
- Weight of product: 0.23 kg
- Operating ambient temperature: 0...60 °C
- Relative humidity: 10...95 % without condensation
- Degree of IP protection: IP20

- Directives: 2014/35 / EU - low voltage directive, 2014/30 / EU - electromagnetic compatibility
- Sustainable supply status: Product Green Premium
- REACH Regulation: Reference does not contain SVHC
- According to REACH without SVCC: Yes
- EU RoHS Directive: Proactive compliance (out-of-scope product of RoHS EU)
- No mercury: Yes
- Information on RoHS exemptions: Yes
- RoHS China Regulations: X
- WEEE: On the European Union market, the product must be disposed of in accordance with a specific waste collection system and never end up in a waste container

Specifications

EAN	3595864024431
Manufacturer	SCHNEIDER
Weight (kg)	0,23 kg
Protection	IP20
Nominal voltage (V)	24

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 13 October 2026