

Product sheet

Modbus RS485 Communication Module 0-248

Brand: SCHNEIDER

Reference: IMPO TPCCOM16



Modbus RTU slave communication module on RS485 interface for integration into automation systems. Supports transmission speeds of 4800, 9600 and 19200 bauds with even parity. Configuration address from 0 to 248. Connection via front-mounted screw terminals, square mounting. Shielded twisted pair cable 1.5 mm².

[View product online](#)

Description

Modbus RS485 slave communication module designed for integration into network control systems, specifically for the TransferPacT Active Automatic device. Enables data transmission using the Modbus RTU protocol at various transmission speeds, facilitating device communication in industrial environments.

Technical features

- Bus type: Modbus
- Physical interface: RS485
- Transmission speeds: 4800, 9600 and 19200 bauds
- Parity: Even
- Communication address: 0...248
- Rated insulation voltage: 30 V DC
- Cable type: Shielded twisted pair 1.5 mm²
- Connections: Stripped screw terminal
- Protection rating: IP20
- Contamination degree: 3
- Mounting: Square connection, front position
- Height: 56.5 mm
- Depth: 69 mm
- Width: 20 mm

- Weight: 40 g
- Tightening torque: 0.6 N·m ± 0.1 N·m
- Category: Communication accessories
- Compliant with EU RoHS and REACH without SVHC
- Green Premium product

Specifications

Width	20 mm
EAN	3606481066060
Manufacturer	SCHNEIDER
Range	Industrial
Long	56,5 mm
Weight (kg)	0,04 kg
Depth	69 mm
Protection	IP20
Nominal voltage (V)	30 V

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 10 October 2026