

Product sheet

TransferPacT Module CAN Extension 24 V

Brand: SCHNEIDER

Reference: IMPO TPCDIO15



TransferPacT module for CAN bus extension and external 24 VDC power supply, designed for integration into signaling systems. Supports connection to external HMI, with 30 V DC electrical isolation, left-bottom mounting position, and screw-type terminal for wire sections from 0.05 to 2.6 mm².

[View product online](#)

Description

TransferPacT module, designed as a CAN bus extension and external 24 VDC power supply, enables enhanced connectivity in signaling systems via CAN interface. Used to connect external devices such as HMI, facilitating communication in industrial environments.

Technical Features

- Function: Signaling
- Signaling function: CAN extension (connect to external HMI) Output voltage (24 V)
- Auxiliary connection terminal: Screw clamp terminal 0.05...2.6 mm²
- Mounting type: Connection
- Mounting position: Left-bottom
- Input current: 1 A 24 V DC +/- 20 %
- [Ui] Nominal insulation voltage: 30 V DC
- Torque: 0.6 N·m +/- 0.1 N·m
- Height: 56.5 mm
- Width: 20 mm
- Depth: 69 mm
- Protection rating IP: IP20
- Contamination degree: 3
- Accessory/component category: Signaling accessory
- Units per package 1: 1

- Units per package 2: 20
- Sustainable offering status: Green Premium product
- Compliant with REACH without SVHC: Yes
- EU RoHS Directive: Compliant
- Mercury-free: Yes
- China RoHS Regulation: X
- RoHS exemption information: Yes

Specifications

Rated current (A)	1
Width	20 mm
EAN	3606481066053
Manufacturer	SCHNEIDER
Long	56,5 mm
# Elements	1
Depth	69 mm
Cable cross-section (mm²)	6 mm²
Nominal voltage (V)	24 V
Current type	DC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 9 October 2026