

Product sheet

Industrial mobile socket 125 A 3P+E IP67

Brand: SCHNEIDER

Reference: IMPO 81494



Industrial mobile socket 3P+E, 125 A, 380-415 V AC, with IP67 and IK08 protection rating. Designed for industrial environments, compatible with IEC 60309-1/2 standard. Features stainless steel and nickel-plated brass contacts, non-loosening screw connections, Pg 48 threaded cable entry, and a self-extinguishing engineering polymer housing.

[View product online](#)

Description

Industrial straight mobile socket designed for high-demand industrial applications requiring safety and durability. Compatible with IEC 60309 standard, rated for 125 A nominal current and 380-415 V AC voltage, operating at 50/60 Hz. Constructed with self-extinguishing engineering polymer and terminals made of stainless steel and nickel-plated brass, ensuring robustness and reliability under harsh conditions.

Technical specifications

- Number of poles: 3P+E
- Rated operating voltage: 380...415 V AC
- Nominal current: 125 A
- Supply frequency: 50/60 Hz
- Earth terminal position: 6 o'clock
- Housing material: Self-extinguishing engineering polymer
- Contact material: Stainless steel (pins), nickel-plated brass (sleeves), stainless steel (springs)
- Connections: Non-loosening screws
- Cable cross-section: 16...70 mm²
- Outer cable diameter: 26...48 mm
- Cable entry: Cable gland
- Thread type: Pg 48

- Protection rating: IP67 according to IEC 60529
- Impact protection rating: IK08 according to EN 62262
- Fire resistance: 850 °C according to IEC 60695-2-1
- Operating ambient temperature: -25...40 °C
- Weight: 1.6 kg
- Dimensions: 131 mm (height) x 131 mm (width) x 325 mm (depth)
- Color: Grey (RAL 7035)
- Voltage code: Red
- Standards: IEC 60309-1, IEC 60309-2
- Compatibility: PratiKa socket
- Sustainable offering status: Green Premium product

Designed for use in industrial environments requiring secure connections resistant to impacts and extreme weather conditions. Its high mechanical strength and IP67 protection make it suitable for outdoor installations or areas exposed to dust and water.

Specifications

Frequency	50/60 Hz
Rated current (A)	125
Width	13,1 cm
Colour	Grey
EAN	3303430814948
Manufacturer	SCHNEIDER
Range	Industrial
Material	Polímero
Weight (kg)	1,6 kg
Depth	32,5 cm
Protection	IP67 - uso externo
Nominal voltage (V)	380...415 V CA

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 10 October 2026