

Product sheet

Industrial Socket 3P+E 125 A IP67

Brand: SCHNEIDER

Reference: IMPO 81694



Industrial 3P+E socket, 125 A, 380-415 V AC, panel mounting, with IP67 and IK08 protection rating. Made of self-extinguishing polymer, contacts in stainless steel and nickel-plated brass. Compatible with EN 60309-1/2 standards, withstands up to 850 °C and operates at 90 % humidity at 20 °C.

[View product online](#)

Description

Industrial PratiKa-type socket, 125 A, 3P+E, designed for low-voltage installations in industrial environments. Compatible with industrial connection standards, provides a secure and durable connection for electrical equipment in demanding conditions.

Technical Features

- Number of poles: 3P+E
- Rated operating voltage: 380...415 V AC
- Rated current: 125 A
- Supply frequency: 50/60 Hz
- Earth terminal position: 6 o'clock
- Housing material: Engineering self-extinguishing polymer
- Contact material: Stainless steel pins and springs, nickel-plated brass sleeves
- Connections: Captive screws, fully loosened
- Wire cross-section supported: 16...70 mm²
- Protection rating: IP67 according to IEC 60529
- Mechanical protection rating: IK08 according to EN 62262
- Fire resistance: 850 °C according to IEC 60695-2-11
- Operating ambient temperature: 35 °C (86400 s)
- Relative humidity: 50 % at 40 °C, 70 % at 30 °C, 90 % at 20 °C
- Compliant standards: EN 60309-1, EN 60309-2

- Color: Grey (RAL 7035)
- Voltage color code: Red
- Product weight: 1.17 kg
- Dimensions: 110 x 114 x 161 mm (width x height x depth)
- Mounting: Panel
- Shape: Straight
- Compatibility code: PratiKa socket
- Sustainable offering status: Green Premium product
- Contains SVHC above threshold (REACH)
- EU RoHS: Proactive compliance (outside scope)
- China RoHS: Outside scope
- RoHS exemptions: Yes
- Contains mercury: No

Specifications

Frequency	50/60 Hz
Rated current (A)	125
Width	114
Colour	Grey
EAN	3303430816942
Manufacturer	SCHNEIDER
Range	Industrial
Long	110
Material	Polímero
Measures	110 x 114 x 161 mm
No. of poles	3P+E
Weight (kg)	1,17
Depth	16,1 cm
Protection	IP67 - uso externo
Cable cross-section (mm²)	16
Nominal voltage (V)	380...415 V
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 13 October 2026