

Product sheet

Industrial mobile socket 63 A 3P+N+E IP67

Brand: SCHNEIDER

Reference: IMPO 81483



Industrial mobile socket 3P+N+E, 63 A, 380-415 V AC, with IP67 protection rating and fire resistance up to 850 °C. Designed for demanding industrial environments, compliant with IEC 60309-2 standard, featuring Pg 36 cable entry and non-loosening screw terminals.

[View product online](#)

Description

Industrial straight mobile socket designed for demanding industrial applications. Compliant with IEC 60309 standard, providing secure and robust connection for low-voltage equipment with a nominal current of 63 A and operating voltage between 380 and 415 V AC. Constructed from engineering-grade self-extinguishing polymer, ensuring thermal stability and high mechanical resistance.

Technical specifications

- Number of poles: 3P+N+E
- Rated operating voltage: 380...415 V AC
- Rated current: 63 A
- Supply frequency: 50/60 Hz
- Earth terminal position: 6 h
- Housing material: Engineering-grade self-extinguishing polymer
- Contacts: Stainless steel pins and springs, nickel-plated brass sleeves
- Terminations: Non-loosening screws
- Cable cross-section: 6...25 mm²
- Outer cable diameter: 17...31 mm
- Cable entry: Cable gland
- Thread type: Pg 36
- Protection rating: IP67
- IK protection rating: IK08
- Fire resistance: 850 °C

- Operating ambient temperature: -25...40 °C
- Weight: 0.783 kg
- Dimensions: 110 mm (height) x 110 mm (width) x 265 mm (depth)
- Color: Grey (RAL 7035)
- Voltage code: Red
- Standards: IEC 60309-1, IEC 60309-2

Adaptable to industrial environments exposed to dust, moisture, and impacts, thanks to its high IP67 and IK08 protection ratings. Its vertical design and non-loosening screw connections facilitate installation and maintenance in confined spaces.

Specifications

Frequency	50/60 Hz
High	110 mm
Rated current (A)	63
Width	110 mm
Colour	Grey
EAN	3303430814832
Manufacturer	SCHNEIDER
Range	Industrial
Material	Polímero
No. of poles	3P+N+E
Weight (kg)	0,783 kg
Depth	265 mm
Protection	IP67 - uso externo
Nominal voltage (V)	380...415 V

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 10 October 2026