

Product sheet

Mechanical timer switch 1 channel 16 A

Brand: SCHNEIDER

Reference: IMPO 15331



Monopolar mechanical time switch of the Acti 9 range, designed for applications in buildings. It allows manual switching of time with a 7-day cycle, supports loads up to 16 A to 250 V AC (pf = 1) and provides an accuracy of ± 1 s/day at 20 °C. Compatible with fluorescent, halogen, incandescent and LED lamps.

[View product online](#)

Description

Mechanical timed switch of the Acti 9 range, designed for applications in buildings.

Technical characteristics

- Number of channels: 1
- Function available: Manual time switching
- Application of the device: Buildings
- Load type: Parallel fluorescent tube with correction 5 x 58 W, 7 x 40 W, 2 x 100 W; Halogen lamp 230 V AC 1000 W; Incandescent lamp 230 V AC 1000 W; Fluocompact lamp 700 VA; Compact fluorescent lamp 150 W; LED lamp; LED lamp > 2 W 300 W
- Cycle duration: 7 days
- Maximum number of switches: 42 activated - 42 disabled
- Minimum interval duration: 2 h
- Adjustment type: Manual hour change
- Measurement accuracy: ± 1 s/day at 20 °C
- Power consumption: 0.5 W
- Maximum switching intensity: 16 A - 250 V AC pf = 1; 4 A - 250 V AC pf = 0.6
- Nominal employment voltage: 230...240 V AC in 50...60 Hz
- Battery life: 10 years
- Backup time: 150 h and savings program
- Mounting bracket: Rail DIN

- 9 mm steps: 2
- Colour tone: White (RAL 9003)
- Connections: Screw terminals
- Width: 18 mm
- Height: 90 mm
- Depth: 66 mm
- Weight: 0.101 kg
- Operating ambient temperature: -10...50 °C
- Degree of IP protection: IP20 B (terminals, status 1)
- EU RoHS Directive: As per
- REACH Regulation: Contains SVHC over the threshold
- No mercury: Yes
- Information on RoHS exemptions: Yes
- RoHS China Regulations: Product outside of RoHS China
- Sustainable supply status: Product Green Premium

Specifications

Rated current (A)	16
Width	18 mm
Colour	White
EAN	3303430153313
Manufacturer	SCHNEIDER
Long	18 mm
Halogen-free	Yes
Weight (kg)	0,101 kg
Power (W)	0,5 W
Maximum power (W)	1000 W
Depth	66 mm
Protection	IP20
Nominal voltage (V)	230...240 V
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 13 October 2026